



PHOS  
ENGINEERING LIGHT

EYECONIC TRIMLESS WALL WASH  
STANDARD

## EYECONIC TRIMLESS WALL WASH - STANDARD

The Eyeconic Trimless Wall Wash is a recessed, fixed downlight with a  $\varnothing 44\text{mm}$  aperture and features a discrete removeable anti-glare guard, wall wash lens and trimless plaster-in frame.

### PRODUCT FEATURES

Downlight

Fixed

Interior

LED

IP65

Available in all Phos finishes

Interchangeable optics & accessories (pre & post install)

### PHOS STANDARDS

60min fire-certified

Acoustic-rated

UK designed, manufactured and assembled

5 year warranty

### OPTICS

Standard beam angles:  
Wall Wash

### PHYSICAL PROPERTIES

Diameter  $\varnothing 80\text{mm}$

Height 70mm (4W/9W)

Height 95mm (14W)

Cut-out  $\varnothing 64\text{mm}$


### DRIVER INFORMATION

[Driver Configurator \(Link\)](#)

### PRODUCT VIEW



### DIMENSIONS



4W & 9W

14W

## TECHNICAL SPECIFICATIONS

CCT	2700K		
Wattage	4W	9W	14W
Beam Angles	WW	WW	WW
Luminaire Lumens (lm)	125	211	262
Circuit Watts (c/W)	6	10.8	16.2
Luminaire Efficacy (l/cW)	21	20	16
Luminance (Cd)	147	243	309
Forward Voltage (Vf)	11.78	12.36	12.65
Current (mA)	350	700	1050

CCT	3000K		
Wattage	4W	9W	14W
Beam Angles	WW	WW	WW
Luminaire Lumens (lm)	131	232	302
Circuit Watts (c/W)	6	10.8	16.3
Luminaire Efficacy (l/cW)	22	21	18
Luminance (Cd)	155	268	354
Forward Voltage (Vf)	11.78	12.36	12.65
Current (mA)	350	700	1050


Binning	2 step MacAdams
CRI	90+
TM-30-15	Rg 101 Rf 90
Lumen Maintenance	LM80
Lifetime	50,000 hours

Dimming Options	Mains dim / Non-dim / 0-10V / DALI (dim to dark 0.01%) / Casambi
Flicker Index	0
SVM: (Visual Flicker)	0.02

Driver distance from fitting	Up to 10m (AWG 20)*
Wiring Type	Series
Accessories	Remote emergency (Maintained / Self Test)


\*If driver distance from fitting is +10m see driver configurator document for guidance

## LIGHT CONES



WW

## POLAR CURVES



WW

## LUMINAIRE PARTCODE BUILDER

Example Code: EY-TW-B1-STD14-30-90-WW-1050

Family	Variant	Socket Finish	Engine	Power	CCT	CRI	Beam Angle	Driver Current
EY Eyeconic	TW Trimless Wall Wash	B1 Anodised Black	STD Standard	4 Watts	27 2700K	90	WW	350
				9 Watts	30 3000K			700
				14 Watts	40 4000K			1050

## FRAME PARTCODE BUILDER

Example Code: TFR-WT

Variant	Frame Finish
TFR Trimless Frame	WT Textured White
	B2 Black