

ALPHABET

</scripting_light>

EXAMPLE OF APPLICATION TAF24 SYSTEM

SUPPLIED BY 48V
ON-OFF/DALI/1-10V
BLUETOOTH

T24P_FEEDER

T24IZ1_SEGMENT WITH 1 SPOT 9W 970Lm

T24JL_LINEAR CONNECTION

T24A084_SEGMENT OF 840mm WITH DIFFUSED LIGHT

T24JD_JOINT DOWN

T24L084_SEGMENT OF 320mm WITH DIFFUSED LIGHT

T24JU_JOINT UP

T24L032_SEGMENT OF 320mm WITHOUT DIFFUSED LIGHT

T24JT_JOINT 'T' SHAPE

T24IF2_SEGMENT WITH 2 SPOT 2*7W 2*970Lm

T24JL_LINEAR CONNECTION

T24A084_SEGMENT OF 840mm WITH DIFFUSED LIGHT

T24JL_LINEAR CONNECTION

T24IF2_SEGMENT WITH 1 SPOT 7W 970Lm

T24JA_JOINT 90°

T24L084_SEGMENT OF 840mm WITHOUT DIFFUSED LIGHT

T24JA_JOINT 90°

T24A084_SEGMENT OF 1880mm WITH DIFFUSED LIGHT

T24L084_SEGMENT OF 320mm WITH DIFFUSED LIGHT

T24IZ1_SEGMENT WITH 1 SPOT 9W 970Lm

T24JL_LINEAR CONNECTION

T24JA_JOINT 90°

