


VERTEX

Functional and Sleek Light Column Family

CE UK CA IK08 IP66 




VERTEX provides uniform light distribution with unique reflector technology and glare reduction with hidden light source.



- Equipped with HEPER's Dyno (DYN) module
- Superior glare management with hidden light source
- Uniform light distribution with advanced reflector technology
- Different height options and matching bollard to complement high-end architectural projects
- Minimalistic design to blend in with different types of architecture
- Modular structure allowing seamless integration

Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control	Weight
LB6064.592-EN	VERTEX 2 Module	[SLFB] 144x41°	846 - 945 lm	15 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off	10.8 kg
LB6064.596-EN	VERTEX 6 Module	[SLFB] 144x41°	2538 - 2835 lm	45 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	22.5 kg

LB6064.592



LB6064.596



[SLFB]

Special linear,
Forward throw

Extras

Consult the factory


120-277V
50/60Hz

UNI

120-277V 50/60Hz


Accessories (To be ordered separately)

Anchorage



628I005
628I005

Anchorage



625J013
625J013

HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications
without prior written notice. Edition: 12.01.2024.
For current version visit heperlighting.com. All
flux (±%7 tolerance) and power values (±%10
tolerance) are derived following appropriate IES,
CIE, and applicable standards.

