



Clean lines, different light distribution options, and jaw-dropping optics make the DRAGO family stand out to illuminate pathways, landscaped areas, and other public spaces.

- Equipped with HEPER's Dyno (DYN) module or high efficiency LED chips with flexible lens optics
- 1 to 6 light distribution ratio with no uplight (DYN)
- Minimized glare with hidden light source
- Indirect lighting with reflector technology
- Optimized linear forward or side throw options with full cut-off and minimized stray light
- Motion sensor & emergency kit options


Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control	Weight
LB6048.575-EN	DRAGO Forward	[SLFB] 65x70°	721 - 2100 lm	10 - 20 W	2200 K CRI 80, 2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	3.53 kg (0.25 m), 4.5 kg (0.8 m)
LB6048.585-EN	DRAGO Side	[SLSB] 145x45°	360 - 1050 lm	5 - 10 W	2200 K CRI 80, 2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	3.53 kg (0.25 m), 4.5 kg (0.8 m)
LB6048.910-EN	DRAGO 8 LED	[T3] 144x57°	709 - 808 lm	9.5 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	3.53 kg (0.25 m), 4.5 kg (0.8 m)
LB6068.570-EN	DRAGO Forward Duo	[SLFB] 65x70°	1442 - 4200 lm	20 - 40 W	2200 K CRI 80, 2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off	4.11 kg (0.25 m), 5.67 kg (0.8 m)
LB6068.571-EN	DRAGO Side Duo	[SLSB] 145x45°	720 - 2100 lm	10 - 20 W	2200 K CRI 80, 2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	4.11 kg (0.25 m), 5.67 kg (0.8 m)
LB7035.575-EN	DRAGO Ex Forward	[SLFB] 65x70°	721 - 2100 lm	10 - 20 W	2200 K CRI 80, 2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	4.50 kg (0.35 m), 6.0 kg (0.8 m)
LB7035.585-EN	DRAGO Ex Side	[SLSB] 145x45°	360 - 1050 lm	5 - 10 W	2200 K CRI 80, 2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	4.50 kg (0.35 m), 6.0 kg (0.8 m)

LB6048.575 / LB6048.585  
LB6048.910


LB6068.570 / LB6068.571

LB7035.575 / LB7035.585



180 mm 133 mm  
7 3/32" 5 15/64"



180 mm 217 mm  
7 3/32" 8 35/64"





180 mm 153 mm  
7 3/32" 6 1/32"




[SLFB]

Special linear,  
Forward throw



[SLSB]

Special linear,  
Side throw




[T3]

Type III,  
Asymmetric,  
Side throw

## Extras

Consult the factory



EK

Emergency kit

Consult the factory



MS

Motion sensor

Consult the factory



UNI

120-277V 50/60Hz

Luminaire body options




DPC

Double powder  
coating

## Accessories (To be ordered separately)

### Anchorage



6281000

6281000

HPR Pazarlama A.Ş.  
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,  
Sincan, 06909 Ankara, Turkey  
+90 312 267 54 30  
info@hepergroup.com

HEPER Europe GmbH  
Ahornweg 5a, 58675  
Hemer, Germany  
+49 237 2901 2975  
infoEU@hepergroup.com

We reserve the right to change specifications  
without prior written notice. Edition: 12.01.2024.  
For current version visit [heperlighting.com](http://heperlighting.com). All  
flux ( $\pm 7\%$  tolerance) and power values ( $\pm 10\%$   
tolerance) are derived following appropriate IES,  
CIE, and applicable standards.

