

TRIAN

Contemporary and Scalable Bollard Family

CE UK CA IK05 IP65 




Eye-catching design and unique optics with a light touch make TRIAN stand out to illuminate pathways, landscaped areas, and other public spaces.



- Equipped with HEPER's Dyno (DYN) module
- Minimized glare with hidden light source
- Optimized linear forward light distribution option with full cut-off and minimized stray light
- Easy installation and maintenance
- Modern and elegant design creating a unique touch in exterior applications

Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control	Weight
LB6020.546-EN	TRIAN	[SLFB] 120x47°	138 - 159 lm	4 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off	8.6 kg
LB6042.545-EN	TRIAN S	[SLFB] 120x47°	69 - 79 lm	3 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off	3.5 kg

LB6020.546



LB6042.545



[SLFB]

Special linear,
Forward throw

Extras

Consult the factory

Luminaire body options

120-277V
50/60Hz

DPC

UNI


120-277V 50/60Hz

DPC

Double powder
coating


Accessories (To be ordered separately)

Anchorage



623J014
623J014

Anchorage



629J014
629J014

HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications
without prior written notice. Edition: 12.01.2024.
For current version visit heperlighting.com. All
flux (±%7 tolerance) and power values (±%10
tolerance) are derived following appropriate IES,
CIE, and applicable standards.

