

ECO LED STICK-LITE

INTEGRAL DRIVER

Code Creator



1	2	3	4
---	---	---	---

- Cat No.**
 ECO LED 2
 ECO LED 4
 ECO LED 5
- CCT – Colour Temperature**
 4k - 4000k
 6k – 6500k
- Cap Colour**
 B – Black
 W – White
- Wire Colour**
 B – Black Cable
 W – White Cable

Cat No.	Length (mm)	Illuminated Length (mm)	Lumens	Circuit Power (W)
ECO LED Stick-Lite 2'	650	500	708	8
ECO LED Stick-Lite 4'	1260	1100	1654	14
ECO LED Stick-Lite 5'	1560	1410	2033	20

Fitting supplied with plastic surface mounting brackets as standard.

Suitable to be suspended horizontally with our suspension kit, please purchase separately.

Fitting can be suspended vertically off its own power cable.

If coloured filter is required, please advise the colour required at time of enquiry

PHOTOMETRICS

		ECO LED 2'	ECO LED 4'	ECO LED 5'	
Photometric Measurements	Luminous Flux (lm)	708	1654	2033	
	Luminous Efficacy (lm/W)	87	123	105	
Electrical Measurements	Frequency (Hz)	50	50	50	
	Voltage (V)	230.2	231.2	230.7	
	Current (A)	0.037	0.062	0.087	
	Power (W)	8.1	13.5	19.3	
	Power Factor	0.958	0.946	0.966	
	Apparent Power (VA)	8.4	14.4	20.0	
	Lifetime (hrs)	30,000	30,000	30,000	
Goniophotometric Measurements	Beam Angle	Horizontal (°)	180	180	180
		Vertical (°)	105	106	106



Tube
Ø 30mm



Cap
Ø 34.5mm



Light Output
290°



For further information

Call: +44 (0)1525 376974 Email: sales@encapsulite.co.uk Visit: www.encapsulite.co.uk