

24V RD TWIN STICK

REMOTE DRIVER

Code Creator



1	2	3	4	5
---	---	---	---	---

1. **Cat No.**
Please select from the table
2. **CCT – Colour Temperature**
3k
4k
3. **Cap Type**
S – Standard
M – Membrane
4. **Cap Colour**
S – Silver (standard cap only)
B – Black
W – White
5. **Wire Colour**
B – Black Cable
W – White Cable
C – Clear Cable

Cat No.	Length (mm)	Illuminated Length (mm)	Lumens	Circuit Power (W)
24V RD TS V2 4	300	240	564	8
24V RD TS V2 5	370	310	729	10
24V RD TS V2 6	445	385	905	12
24V RD TS V2 7	515	455	1069	13
24V RD TS V2 8	585	525	1234	15
24V RD TS V2 9	660	600	1410	17
24V RD TS V2 10	730	670	1574	18
24V RD TS V2 11	800	740	1739	20
24V RD TS V2 12	875	815	1915	22
24V RD TS V2 13	945	885	2079	24
24V RD TS V2 14	1015	955	2245	25
24V RD TS V2 15	1085	1025	2409	28
24V RD TS V2 16	1160	1100	2585	29
24V RD TS V2 17	1230	1170	2750	31
24V RD TS V2 18	1300	1240	2914	33
24V RD TS V2 19	1375	1315	3091	35
24V RD TS V2 20	1445	1385	3255	36
24V RD TS V2 21	1515	1455	3420	38
24V RD TS V2 22	1590	1530	3596	40
24V RD TS V2 23	1660	1600	3760	42
24V RD TS V2 24	1730	1670	3925	44
24V RD TS V2 25	1800	1740	4089	45
24V RD TS V2 26	1875	1815	4266	47
24V RD TS V2 27	1945	1885	4430	49
24V RD TS V2 28	2015	1955	4594	51

Fitting supplied with plastic surface mounting brackets as standard. Slotted brackets available

Suitable to be suspended horizontally or vertically with our suspension kit, please purchase separately.

Cable entry through end cap as standard, if rear entry cable is required, please let us know.

Coloured sleeves available, please let us know if required.

If fitting longer than lengths listed is required, please contact us.

Drivers sold separately, please see table across for options.



Tube
Ø 30mm



Cap
Ø 33mm



Light Output
360°

Wattages	Dimming Protocol				
	Fixed	Dali	LTE*	1-10V	DMX
30	○				
100	○	○	○	○	○
150		○			

*LTE – Leading / Trailing Edge



For further information

Call: +44 (0)1525 376974 Email: sales@encapsulite.co.uk Visit: www.encapsulite.co.uk