

ECO LED STICK-LITE IP64

INTEGRAL DRIVER



1

2

- Cat No.**
 ECO LED 2 WP
 ECO LED 4 WP
 ECO LED 5 WP
- CCT – Colour Temperature**
 4k - 4000k
 6k - 6500k

Fitting supplied with plastic surface mounting brackets as standard.

Fitting supplied with black caps and cable only.

Suitable to be suspended horizontally or vertically with our suspension kit, please purchase separately.

Coloured sleeves available, please let us know if required.



Cat No.	Length (mm)	Illuminated Length (mm)	Lumens	Circuit Power (W)
ECO LED Stick-Lite IP64 2'	700	490	708	8
ECO LED Stick-Lite IP64 4'	1310	1100	1654	14
ECO LED Stick-Lite IP64 5'	1610	1400	2033	20

PHOTOMETRICS

		ECO LED IP64 2'	ECO LED IP64 4'	ECO LED IP64 5'
Photometric Measurements	Luminous Flux (lm)	708	1654	2033
	Luminous Efficacy (lm/W)	87	123	105
Electrical Measurements	Frequency (Hz)	50	50	50
	Voltage (V)	230.2	231.2	230.7
	Current (A)	0.037	0.062	0.087
	Power (W)	8.1	13.5	19.3
	Power Factor	0.958	0.946	0.966
	Apparent Power (VA)	8.4	14.4	20.0
	Lifetime (hrs)	30,000	30,000	30,000
Goniophotometric Measurements	Beam Angle	Horizontal (°)	180	180
		Vertical (°)	105	106



For further information

Call: +44 (0)1525 376974 Email: sales@encapsulite.co.uk Visit: www.encapsulite.co.uk