


VERTEX C

Functional and Sleek Recessed Luminaire

CE UK CA IK08 IP66 




Its recessed body, precise optics, and minimalist design make VERTEX stand out for contemporary architectural projects.

- Equipped with HEPER's Dyno (DYN) module
- Superior glare management with hidden light source
- Indirect lighting with reflector technology
- Uniform light distribution with advanced reflector technology
- Modular structure allowing seamless integration



Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control	Weight
LD6064.591-EN	VERTEX C 1 Module	[WW] 45x55°	423 - 473 lm	8 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	0.72 kg

LD6064.591

141 mm
5 35/64"



57 mm
2 1/4"



[WW]

Wall-wash


Extras

Consult the factory

120-277V
50/60Hz

UNI

120-277V 50/60Hz



[HM1]

Black

HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 31.01.2024. For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.