

ULTRA EFFICIENCY 90

Linear strip with ultra efficiency >165 lm/w and cri90
 Ruban ultra efficacité >165 lm/w et cri90

A4190



Indice de Rendu de Couleur IRC **Color Rendering CRI**
 >90

Temperature de couleur **Color CCT**
 2700K - 3000K - 4000K - 6500K

@4000K - Rendement **Luminous Efficacy**
 160 lm/w









Puissance & nombre de led **Power & number of Led**
 21 w/m & 160 led/m | 18 w/m & 128 led/m
 12 w/m & 80 led/m | 9.6 w/m & 64 led/m

Coupe **Cut**
 50 mm (21w) | 62.5 mm (18w) | 100 mm (12w) | 125 mm (9.6w)

Dimensions **Dimensions**
 5000 x 10 x 2 mm

Température d'utilisation **Ambiant temp.**
 - 10°C / + 40°C

Tension d'alimentation **Input voltage**
 24 Vdc



A4190.21.160.927.IP20.DALI

Power & number led/m

21 w/m & 160 led/m (160 lm/w @4000K)	21.160
18 w/m & 128 led/m (160 lm/w @4000K)	18.128
12 w/m & 80 led/m (160 lm/w @4000K)	12.80
9.6 w/m & 64 led/m (160 lm/w @4000K)	09.64

Led Color

	9.6 w/m	12 w/m	18 w/m	21 w/m	
2700K	1344 lm	1680 lm	2520 lm	2940 lm	927
3000K	1411 lm	1764 lm	2646 lm	3087 lm	930
4000K	1536 lm	1920 lm	2880 lm	3360 lm	940
6500K	1536 lm	1920 lm	2880 lm	3360 lm	965

IP Rating

IP 20	IP20
IP 54	IP54
IP65H	IP65

Dimming

No dimming	HF
Dali	DALI
Dmx	DMX
Dimming I to 10VDC	D10
Phase dimming	PHA