

ORUS

Tiny cylindrical profile
Profil cylindrique miniature

A3990




Puissance maxi Power max
12 w/m

Dimensions Dimensions
D 12 mm

Longueur maximale Max.length
3000 mm

Température d'utilisation Ambient temp.
- 10°C / + 40°C




A3990.00
Silver Grey ano




A3990.04
Black anodised



A3990.16
White RAL9016



A3990.FR
Frost cover



A3990.ND
Night&Day cover



A3990.OP
Opal cover

A3990.COB4.IP20.00.OP.DALI

Type of led

Cob 8 mm 10w A4130
Cob 4 mm 8w A4130
Slim 8 (ultra cri) A4118
Slim 5 A4110

COB8
COB4
S8
S5

IP Rating

IP20
IP54
IP65H

IP20
IP54
IP65

Finishes

Aluminium anodised silver
Aluminium anodised black

00
04

Cover & Optic

Opal
Frost
Night & Day

OP
FR
ND

Dimming

No dimming
Dali
Dmx
Dimming & to 10Vdc
Phase Dimming Digital

HF
DALI
DMX
D10
PHD




A3990.CLP.00
Endcap grey



A3990.CLP.04
Endcap black



A3990.CLP.16
Endcap white



A3990.CLI
Clips stainless steel



A4130
COB led strip - no dots



A3990.ND
Night&Day version