

□ NODO MICROLED



NODO MICROLED

180 LED/m - 11W/m - 24V

100 cm - 3000K 1100 lm/m


63010 Silver Argento

200 cm - 3000K 1100 lm/m

63020 Silver Argento

300 cm - 3000K 1100 lm/m

63030 Silver Argento



Special sizes upon request.
Misure speciali su richiesta.

Aluminium dimmable LED profile. Attachment to the track using the integrated double sided tape. The electric installation is independent from the system. Photometric measure LETROH.com

Profilo LED dimmerabile in alluminio. Fissaggio al binario mediante biadesivo integrato. L'installazione elettrica rimane indipendente dal sistema. Curve fotometriche LETROH.com

◆ IP20 CE Kg 0,10/100 cm


LetroH.com



Not dimmable power supply
Alimentatore non dimmerabile

25120 70W

INPUT 220/240V AC 50/60 Hz
OUTPUT 24V - 70W / 150W



Constant voltage power supply. Not dimmable. Combined with dimmer 40209 it allows dimming of the LED bar. It must be housed remotely from the installation.

Alimentatore a tensione costante. Non dimmerabile. Abbinato al dimmer 40209 consente la dimmerazione della barra LED. Deve essere alloggiato in posizione remota rispetto all'installazione.

IP20 CE Kg 0,30



Dimmer - Mono PWM
[0-10V, 1-10V, Push, POT, DALI]

40209 Dimmer


INPUT 24V DC
OUTPUT 24V DC

Optional
Opzionale

25162 CASAMBI Dimmer

25160 CASAMBI Remote control

The Casambi 25162 device, combined with 40209, allows the installation to be controlled via Bluetooth. Il dispositivo Casambi 25162, abbinato al 40209, permette il controllo via Bluetooth dell'installazione.



Single-channel dimmer with PWM voltage output. Control inputs: isolated button, DALI, isolated boost (100K), passive 0-10V (not insulated), passive 1-10V (not insulated).

Dimmer monocanale con uscita in tensione PWM. Ingressi di controllo: pulsante isolato, DALI, potenziamento isolato (100K), 0-10V passivo (non isolato), 1-10V passivo (non isolato).

IP20 CE Kg 0,15



NODO track has been studied to integrate the optional LED light easily and hidden from view. MICROLED is dimmable and available in 3000K version. When the track is suspended from the ceiling, the LED light is in a Up Light position for indirect ambient lighting. When the track is fixed on a horizontal or vertical surface, the LED light is placed in the Side Light position for diffused lighting on the surface.

La forma del binario NODO è stata studiata per integrare, con facilità e nascosta alla vista, la luce LED opzionale. MICROLED è dimmerabile e disponibile in versione 3000K. Quando il binario viene sospeso a soffitto la luce LED si colloca in posizione Up Light per l'illuminazione indiretta dell'ambiente. Fissando il binario su un piano orizzontale o verticale la luce LED, grazie alla posizione Side Light, crea un'illuminazione diffusa sul piano.



LETROH Srl
Via Cadorna 15
20073 Opera [Milano] Italia
contact@letroh.com
letroh.com

