



common ipx

RECESSED DOWNLIGHT

LIGHTSOURCE BY
XICATO




Aluminium recessed downlight. Available in anodised aluminium or painted white RAL9003 tex.

LED source Xicato XIM.

Available standard in 700 lm output.

Beam option 40° and 60°.

Protection index IP44.



REF	A6125A common ipx alu A6125W common ipx white
LED	Xicato XIM
LED LM OUTPUT	700 lm
POWER CONS.	5,6 W
COLOR TEMP.	2.700/3.000/4.000 K
CRI/GAI	80
REFLECTOR	40°/60°
FINISH	anodised aluminium / white RAL9003 tex
ADJUSTABLE	n/a
CUT-OUT	Ø 80 mm with blade springs
DRIVE CURRENT	350 mA
REMARK	also available as MR16/GU10 downlight A2034 common IP A2035 common IP white

MODEL	REFERENCE	LUMEN OUTPUT	CRI / COLOR TEMPERATURE	BEAM	DIMMING OPTION
common ipx alu common ipx white	A6125A A6125W	700 lm	8027	20° 40°	PD (phase dimming) ND (non dimmable)
			8030		
			8040		

ORDER CODE: MODEL N° + LUMEN OUTPUT + CRI / COLOR TEMPERATURE / GAI + BEAM ANGLE + DIMMING OPTION
F.E.: A60°/700lm/8030/40°/ND