



MiMi Code Table



Housing/Finish	Cover/Lens	LED Type	Colour (CCT)	Length Availability	IP Rating	Connection Type	Voltage				
MiMi, Silver anodised	MISA	Clear cover	B	n- 504 ³ n504	2100K	21K	MiMi 352 M 103.3-2020mm 83.3mm increments	IP54 54	300mm Single tail	c1	24V DC g
					2300K	23K	MiMi 007 M 61.7-2020mm 41.7mm increments	IP67 ² 67	300mm Double tail	c2	
	Diffused cover	C	s- 352 s352	2500K	25K	MiMi 504 M 120-2020mm 100mm increments	300mm Single IP54 connector ³	c5			
				2700K	27K	MiMi 508 M 91.4-2020mm 71.4mm increments		c6			
				3000K	30K	MiMi 207 M 103.3-2020mm 83.3mm increments		c7			
				3200K	32K	MiMi 208 M 186.7-2020mm 166.7mm increments		c8			
				3500K	35K	MiMi RGB M 103.3-2020mm 83.3mm increments					
				3800K	38K						
			e- 007 e007	5000K	50K						
				508 e508	RED	RED	s- s352, s007, s504 only				
					GREEN	GRN					
				207 ¹ d207	BLUE	BLU					
				208 ¹ d208	ORANGE	ORN					
			RGB d501	AMBER	AMB						
				RGB	RGB						

¹ LEDmix requires two colour temperature choices

² Due to the clear, flush potted polyurethane top layer on IP67 MiMi a colour shift of +/-20K should be expected

³ n-line: 2700K / 3000K

Code Example:

MISA	-	C	-	s504	-	35K	-	M 520	-	67	-	c5	-	g
MiMi, Silver anodised		Diffused cover		s-line 504		3500K		520mm		IP67		300mm Single IP54 connector		24V DC

¹ LEDmix Code Example:

MISA	-	C	-	d207	-	21	-	35	-	M 520	-	67	-	c5	-	g
MiMi, Silver anodised		Diffused cover		LEDmix 207		2100K		3500K		520mm		IP67		300mm Single IP54 connector		24V DC