




PRODUCT SPECIFICATION


Dimension	L5000/W14mm
PCB increment	Power connection and cut point every 25mm
LED pitch	4.17mm
Chip	Epistar
Beam angle	120°
Colours	White
Bin/step	3 Step MacAdam ellipse
CRI	95.8
Lifetime	50000hrs @45°
Operating temp.	0 - 50°C
IP rating	IP0.37/037/0370
Mounting	3M VHB backing tape
Minimum bend radius	10mm
Connection	Hardwire tails or male/female connectors
Control	0-10V/1-10V/DMX/DALI



PERFORMANCE DATA (for 1000mm)

Power consumption	18.75W
Supply voltage	24V DC
Supply current	0.781A
Luminous flux	1317.1Lm/M

TECHNICAL DRAWING



PRODUCT DETAILS

Product name	ECO FLEX 240 DL
Stated output	1317.1lm per metre
Description	Flexible LED Tape, 4000K, 24V, 18.75W/m
Quantity/length of product tested	1 x 1000mm
Bin tolerance/#. MacAdams ellipse of chip	3 Step MacAdam ellipse

ELECTRICAL CHARACTERISTICS

Input Voltage (V DC)	24
Input power (W DC)	18.75
Input Current (mA DC)	781mA

LIGHT OUTPUT

Total light output (Lumens)	1317.1
Luminaire efficacy (lm/W)	70.25
Beam angle	120°


COLOUR CHARACTERISTICS

Correlated colour temperature (CCT)	4109K
Colour rendering index (CRI, Ra)	95.8
Chromaticity coordinates (CIE 1931 - x,y)	0.3740, 0.3668

COLOUR RENDERING INDEX

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
97	97	94	95	95	93	98	96	91	91	94	71	98	96	97

CHROMATICITY DIAGRAM



SPECTRAL RADIANT FLUX VERSUS WAVELENGTH

