


■ PRODUCT SPECIFICATION


Dimension	L5000/W10mm
PCB increment	Power connection and cut point every 71.44mm
LED pitch	8.93mm
Chip	Epistar
Beam angle	120°
Colours	White
Bin/step	3 Step MacAdam ellipse
CRI	93.8
Lifetime	50000hrs @45°
Operating temp.	0 - 50°C
IP rating	IP20/54
Mounting	3M VHB backing tape
Minimum bend radius	10mm
Connection	Hardwire tails or male/female connectors
Control	0-10V/1-10V/DMX/DALI



■ PERFORMANCE DATA (for 1000mm)

Power consumption	15.23W
Supply voltage	24V DC
Supply current	0.635A
Luminous flux	1831.4lm/M

TECHNICAL DRAWING



PRODUCT DETAILS

Product name	LUMEN LINE 112
Stated output	1831.4lm per metre
Description	Flexible LED Tape, 4000K, 24V, 15.23W/m
Quantity/length of product tested	1 x 1000mm
Bin tolerance/#. MacAdams ellipse of chip	3 Step MacAdam ellipse

ELECTRICAL CHARACTERISTICS

Input Voltage (V DC)	24
Input power (W DC)	15.23
Input Current (mA DC)	635mA

LIGHT OUTPUT

Total light output (Lumens)	1831.4
Luminaire efficacy (lm/W)	120.25
Beam angle	120°


COLOUR CHARACTERISTICS

Correlated colour temperature (CCT)	4053K
Colour rendering index (CRI, Ra)	93.8
Chromaticity coordinates (CIE 1931 - x,y)	0.3783, 0.3760

COLOUR RENDERING INDEX

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
95	96	94	93	92	92	97	92	80	88	91	66	95	96	94

CHROMATICITY DIAGRAM



SPECTRAL RADIANT FLUX VERSUS WAVELENGTH

