


■ PRODUCT SPECIFICATION

Dimension	L5000/W10mm
PCB increment	Power connection and cut point every 25mm
LED pitch	4.17mm
Chip	Epistar
Beam angle	120°
Colours	White
Bin/step	3 Step MacAdam ellipse
CRI	92.5
Lifetime	50000hrs@45°
Operating temp.	0 - 50°C
IP rating	IP20/54
Mounting	3M VHB backing tape
Minimum bend radius	10mm
Connection	Hardwire tails or male/female connectors
Control	0-10V/1-10V/DMX/DALI





■ PERFORMANCE DATA (for 1000mm)

Power consumption	23.82W
Supply voltage	24V DC
Supply current	0.993A
Luminous flux	1865.2Lm/M

TECHNICAL DRAWING

IP 20/54



■ PRODUCT DETAILS

Product name	LUMEN LINE 240
Stated output	1865.2lm per metre
Description	Flexible LED Tape, 4000K, 24V, 23.82W/m
Quantity/length of product tested	1 x 1000mm
Bin tolerance/#. MacAdams ellipse of chip	3 Step MacAdam ellipse

■ ELECTRICAL CHARACTERISTICS

Input Voltage (V DC)	24
Input power (WDC)	23.82
Input Current (mA DC)	993mA

■ LIGHT OUTPUT

Total light output (Lumens)	1865.2
Luminaire efficacy (lm/W)	78.3
Beam angle	120°


■ COLOUR CHARACTERISTICS

Correlated colour temperature (CCT)	4136K
Colour rendering index (CRI, Ra)	92.5
Chromaticity coordinates (CIE 1931 - x,y)	0.3739, 0.3704

COLOUR RENDERING INDEX

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
95	94	95	90	93	93	89	91	89	89	94	71	94	98	92

CHROMATICITY DIAGRAM



SPECTRAL RADIANT FLUX VERSUS WAVELENGTH

