

## GENERAL SPECIFICATION

**Body and trim:** Aluminium.

**Finish:** Powder coated.

**Diffuser:** Protruding Lens (2.1mm/0.08").


**Drivers:** Remote, HPF electronic drivers for 120-277V (EU-240V), 0-10V, 1% dimming standard (max distance 20ft).

**Remote Emergency:** Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).


**L70 @25deg C:** > 50,000 hrs.

**Delivered Lumens:** Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.


## MOUNTINGS & OPTICS




Interior - Surface Mounted-Ceiling-Inside




Interior - Surface Mounted-Ceiling-Outside




Interior - Surface Mounted-Wall-Inside




Interior - Surface Mounted-Wall-Outside




95 5105




95 5110




95 5120




95 5130




95 5140




95 5205




95 5210



95 5220



95 5230



95 5240

## HOW TO ORDER

### A SPECIFY LUMINAIRE

Code:	Diameter (A):	Power (LED):	Light Distribution:	Delivered lms:	LPW:
95 5105	660mm/26"	24W	Outside	1440	60
95 5110	914mm/36"	33W	Outside	1980	60
95 5120	1219mm/48"	44W	Outside	2640	60
95 5130	1524mm/60"	57W	Outside	3420	60
95 5140	1829mm/72"	69W	Outside	4140	60
95 5205	660mm/26"	24W	Inside	1344	56
95 5210	914mm/36"	33W	Inside	1848	56
95 5220	1219mm/48"	44W	Inside	2464	56
95 5230	1524mm/60"	57W	Inside	3192	56
95 5240	1829mm/72"	69W	Inside	3864	56

### B SPECIFY CCT/COLOUR (OUTSIDE)

T30	3000K (min 80 CR)
T35	3500K (min 80 CR)
T40	4000K (min 80 CR)
TRD	Red
TGN	Green
TBL	Blue

### C SPECIFY CCT/COLOR (INSIDE)

S30	3000K (min 80 CR)
S35	3500K (min 80 CR)
S40	4000K (min 80 CR)
SRD	Red
SGN	Green
SBL	Blue

### D SPECIFY FINISH

BL	Black
MS	Metallic Silver
WH	White

### E SPECIFY LUMEN & WATTAGE REDUCTION

PRO	Lumen & Wattage Reduction to approximately 25% of standard output
PR1	Lumen & Wattage Reduction to approximately 50% of standard output
PR2	Lumen & Wattage Reduction to approximately 75% of standard output

#### Additional Information

*Note: Custom Reduction Percentages Available Upon Request.*


F SPECIFY OPTIONS

RE Remote Emergency System

EXAMPLE SPECIFICATION CODE

955105/T35/WH

## DIMENSIONAL DIAGRAMS



## APPROVALS

