

## GENERAL SPECIFICATION

**Body and trim:** Steel and aluminum.

**Finish:** Powder coated.

**Diffusers:** Opal polycarbonate supplied in sections.

**Drivers: For RGBW,** integral HPF electronic drivers/DMX interfaces for 120-277V (EU-240V). Luminaires require a DMX controller by others.

**L70 @25deg C:** > 50,000 hrs.

**Delivered Lumens:** Delivered lumens & LPW based on 4000K (min 80 CRI) for White LEDs only.

**Approvals:** Damp Location (Indoor use only).

## MOUNTING & OPTICS



Ceiling



RGBW

## HOW TO ORDER

### A SPECIFY LUMINAIRE

Code:	Diameter (A):	Direct:	Wattage:	Delivered lms:	LPW:
95 1500	610mm/24"	RGBW	22W	2719	124
95 1510	914mm/36"	RGBW	34W	4246	125
95 1570	1219mm/48"	RGBW	46W	5690	124
95 1520	1524mm/60"	RGBW	61W	7427	122
95 1580	1829mm/72"	RGBW	73W	8983	123
95 1530	2133mm/84"	RGBW	88W	10960	125


### B SPECIFY FINISH

BL	Black
MS	Metallic Silver
WH	White
Z1	Wood Grain - Light Cherry
Z2	Wood Grain - Dark Walnut

### EXAMPLE CODE

951500/BL

## DIMENSIONAL DIAGRAMS



## APPROVALS

