

INSIDE/OUTSIDE



GENERAL SPECIFICATION

Body and trim: Aluminium.

Finish: Powder coated.

Diffuser: Protruding Lens (2.1mm/0.08").


Drivers: Remote, HPF electronic drivers for 120-277V (EU-240V), 0-10V, 1% dimming standard. Wire size 18 AWG - max distance (from fixture to drivers) 40', wire size 16 AWG - max distance 60', wire size 14 AWG - max distance 90'. Drivers must be accessible after installation.

Remote Emergency: Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

L70 @25deg C: > 50,000 hrs.

Delivered Lumens: Delivered lumens & LPW based on 4000K (min 80 CRI) for White LEDs only.


MOUNTING & OPTICS




Ceiling
Inside/Outside




Wall Inside/Outside




95 2405




95 2410



95 2420



95 2430



95 2440

HOW TO ORDER

A SPECIFY LUMINAIRE

Code:	Diameter (A):	Power (LED):	Delivered lms:	LPW:	Mounting Points:
95 2405	660mm/26"	46W	2801	61	3
95 2410	914mm/36"	66W	4019	61	3
95 2420	1219mm/48"	87W	5297	61	3
95 2430	1524mm/60"	111W	6759	61	3
95 2440	1829mm/72"	137W	8373	61	4

B SPECIFY CCT/COLOR (OUTSIDE)

T30	3000K (min 80 CR)
T35	3500K (min 80 CR)
T40	4000K (min 80 CR)
TRD	Red
TGN	Green
TBL	Blue

C SPECIFY CCT/COLOR (INSIDE)

S30	3000K (min 80 CR)
S35	3500K (min 80 CR)
S40	4000K (min 80 CR)
SRD	Red
SGN	Green
SBL	Blue

D SPECIFY FINISH

BL	Black
MS	Metallic Silver
WH	White

E SPECIFY LUMEN & WATTAGE REDUCTION

PRO	Lumen & Wattage Reduction to approximately 25% of standard output
PR1	Lumen & Wattage Reduction to approximately 50% of standard output
PR2	Lumen & Wattage Reduction to approximately 75% of standard output

Additional Information

Note: Custom Reduction Percentages Available Upon Request.

F SPECIFY OPTIONS

RE	Remote Emergency System
----	-------------------------

G SPECIFY SURFACE MOUNTING KITS

- BJ2** Surface mounting kit 31.75mm/1.25" extension c/w 3 spacers
- BK2** Surface mounting kit 69.85mm/2.75" extension c/w 3 spacers
- BJ3** Surface mounting kit 31.75mm/1.25" extension c/w 4 spacers
- BK3** Surface mounting kit 69.85mm/2.75" extension c/w 4 spacers

Additional Information

Note: BJ2 & BJ3 are standard, BK2 & BK3, optional

EXAMPLE CODE

952405/T35/S35/WH

DIMENSIONAL DIAGRAMS



APPROVALS

