

# THE LUX COMPANY Dela HE/SUS LED Pendant Can with Philips DLM Flex




THE  
LUX  
COMPANY

## DESCRIPTION



Surface mounted or pendant luminaire fitted with a highly specular reflector and designed for applications with restricted access or no ceiling void. Built around the Philips DLM Flex module and Xitanium driver for optimum performance and long life, it offers a range of lumen outputs, dimming options, a choice of accessories and colour combinations.

## SPECIFICATIONS



Nominal weight	3 kg
Mains voltage	220 - 240 V
Mains frequency	50 - 60 Hz
Ingress protection (front)	IP20
Ingress protection (rear)	IP20
Operating ambient temperature	-25°C to +35°C
Colour consistency - MacAdam Ellipse	3 SDCM
Warranty	5 years
Power factor	>0.9
Colour rendering	R <sub>a</sub> 80

### SURFACE MOUNTED



### PENDANT





## PERFORMANCE DATA

Colour Temp (K)	Luminaire Output (Llm)	Luminaire Power (W)	Luminaire Efficacy (Llm/W)	UGR	Model Ref
3000	1056	15.1	70.1	14.7	HE001/XYZ
3000	1758	25.1	70.1	16.4	HE003/XYZ
3000	2508	33.9	74.1	17.7	HE005/XYZ
3000	3434	48.2	71.3	18.8	HE007/XYZ
4000	1155	15.1	76.7	15.0	HE002/XYZ
4000	1924	25.2	76.4	16.8	HE004/XYZ
4000	2737	34.0	80.6	18.0	HE006/XYZ
4000	3749	48.3	77.7	19.1	HE008/XYZ

## LIFE

Model Ref	25°C Ambient Temperature		
	L90 / B10	L80 / B10	L70 / B10
HE001/XYZ	20,000 h	43,000 h	>60,000 h
HE002/XYZ	20,000 h	43,000 h	>60,000 h
HE003/XYZ	20,000 h	43,000 h	>60,000 h
HE004/XYZ	20,000 h	43,000 h	>60,000 h
HE005/XYZ	20,000 h	42,000 h	>60,000 h
HE006/XYZ	20,000 h	42,000 h	>60,000 h
HE007/XYZ	17,000 h	37,000 h	59,000 h
HE008/XYZ	17,000 h	37,000 h	59,000 h

"L VALUE" = % of initial lumens maintained after specified time

"B VALUE" = % of fittings that will have depreciated below the L value after specified time

### EXAMPLE - 50,000 hours L70 / B50

"L70" = 70% of initial lumens maintained after 50,000 hours

"B50" = 50% of fittings will have depreciated below 70% of the initial lumens after 50,000 hours

OR 50% of fittings will have maintained 70% of the initial lumens after 50,000 hours



## OPTIONS



**T+DALI**  
Touch dimming / DALI



**/SUS**  
2 m suspension kit in white




**/SUS**  
2 m suspension kit in grey



**/SUS**  
2 m suspension kit in black

## FINISHES



**MIX OR MATCH**  
Finishes may be mixed or matched as required



**/WWW**  
White finish



**/GGG**  
Grey finish



**/BBB**  
Black finish



**Example: /WGB**  
White, grey, black

## ACCESSORIES (FACTORY FIT ONLY)



**TA310/FROST**  
Frosted vertical halo



**TA310/BLUE**  
Blue vertical halo



**TA340**  
Clear glass



**TA341**  
Centre etched glass



**TA342**  
Fully etched glass



**TA343**  
Clear polycarbonate



**TA344**  
Opal polycarbonate