

GENERAL SPECIFICATION

Body: Aluminium.

Finish: Powder coated.

Diffusers: Frosted acrylic. Lens protrudes 4.8mm/0.19".

Drivers: Remote, HPF electronic drivers for 120-277V (EU-240V), 0-10V, 1% dimming standard. Wire size 18 AWG - max distance (from fixture to drivers) 40', wire size 16 AWG - max distance 60', wire size 14 AWG - max distance 90'. Drivers must be accessible after installation.

L70 @25deg C: > 50,000 hrs.

Delivered Lumens: Delivered lumens & LPW based on 4000K (min 80 CRI) for White LEDs only.


MOUNTING & OPTICS




Ceiling Direct/Indirect




Ceiling Direct




Wall Direct/Indirect




Wall Direct




98 3615




98 3625




98 3635




98 3645




98 3655




98 3665




98 3715




98 3725




98 3735



98 3745



98 3755



98 3765

HOW TO ORDER

A SPECIFY LUMINARIE LENGTH

Code:	Length:	Power (LED):	Light Direction:	Delivered lms (Length):	LPW:
98 3615	610mm/24"	13W	Direct	1650	125
98 3625	914mm/36"	20W	Direct	2474	124
98 3635	1219mm/48"	27W	Direct	3300	124
98 3645	1524mm/60"	33W	Direct	4124	124
98 3655	1803mm/71"	40W	Direct	4948	124
98 3665	2108mm/83"	47W	Direct	5774	124
98 3715	610mm/24"	16W	Direct/Indirect	2018	126
98 3725	914mm/36"	24W	Direct/Indirect	3026	126
98 3735	1219mm/48"	32W	Direct/Indirect	4034	126
98 3745	1524mm/60"	40W	Direct/Indirect	5044	126
98 3755	1803mm/71"	48W	Direct/Indirect	6052	126
98 3765	2108mm/83"	56W	Direct/Indirect	7060	126

Additional Information

Calculate total lumens and wattage by adding the Length lumens to the Width lumens. For example: direct only 36" length + 48" width = 2474 + 3300 = 5774 total lumens.

B SPECIFY WIDTH

Code:	Width:	Power (LED):	Light Direction:	Delivered lms (Width):	LPW:
WD24	610mm/24"	13W	Direct	1650	125
WD36	914mm/36"	20W	Direct	2474	124
WD48	1219mm/48"	27W	Direct	3300	124
WD60	1524mm/60"	33W	Direct	4124	124
WD71	1803mm/71"	40W	Direct	4948	124
WD83	2108mm/83"	47W	Direct	5774	124
WDI24	610mm/24"	16W	Direct/Indirect	2018	126
WDI36	914mm/36"	24W	Direct/Indirect	3026	126
WDI48	1219mm/48"	32W	Direct/Indirect	4034	126
WDI60	1524mm/60"	40W	Direct/Indirect	5044	126
WDI71	1803mm/71"	48W	Direct/Indirect	6052	126
WDI83	2108mm/83"	56W	Direct/Indirect	7060	126

C SPECIFY CCT/COLOR (DIRECT)

D30	3000K (min 80CRI)
D35	3500K (min 80CRI)
D40	4000K (min 80CRI)
DRD	Red
DGN	Green
DBL	Blue

D SPECIFY CCT/COLOR (INDIRECT)

N30	3000K (min 80CRI)
N35	3500K (min 80CRI)
N40	4000K (min 80CRI)
NRD	Red
NGN	Green
NBL	Blue

E SPECIFY FINISH

Z1	Wood Grain - Light Cherry
Z2	Wood Grain - Dark Walnut

F SPECIFY LUMEN & WATTAGE REDUCTION

PR1	Lumen & Wattage Reduction to approximately 50% of standard Output
PR2	Lumen & Wattage Reduction to approximately 75% of standard Output



Additional Information

PR1 is not available with 983615. Lumen reduction available for direct light only. Custom reduction percentages available upon request.

EXAMPLE CODE

983615/W36/D30/NGN/Z2

DIMENSIONAL DIAGRAMS



APPROVALS



DAMP
LOCATION



IP20

ADA