

GENERAL SPECIFICATION

Body: Aluminium.

Finish: Powder coated.

Diffusers: Frosted acrylic.

Drivers: Remote, HPF electronic drivers for 120-277V (EU-240V), 0-10V, 1% dimming standard. Wire size 18 AWG - max distance (from fixture to drivers) 40', wire size 16 AWG - max distance 60', wire size 14 AWG - max distance 90'. Drivers must be accessible after installation.


L70 @25deg C: > 50,000 hrs.

Delivered Lumens: Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.


MOUNTING & OPTICS




Interior - Surface
Mounted-Ceiling-
Inside/Outside




Interior - Surface
Mounted-Wall-
Inside/Outside




98 2505




98 2510




98 2520




98 2530




98 2540




98 2550




98 2560




W14




W25




W36




W48



W60



W72



W84

HOW TO ORDER

A SPECIFY LUMINAIRE LENGTH

| Code: | Length: | Power (LED): | Delivered lms (Length): | LPW: |
|---------|------------|--------------|-------------------------|------|
| 98 2510 | 635mm/25" | 20W | 2390 | 119 |
| 98 2520 | 915mm/36" | 30W | 3584 | 119 |
| 98 2530 | 1219mm/48" | 40W | 4780 | 119 |
| 98 2540 | 1524mm/60" | 50W | 5974 | 120 |
| 98 2550 | 1829mm/72" | 60W | 7168 | 119 |
| 98 2560 | 2134mm/84" | 70W | 8364 | 120 |

Additional Information

Calculate total lumens by adding the Length lumens to the Width lumens. For example: 36" length x 48" width = 3584 + 4780 = 8364 total lumens.

B SPECIFY WIDTH

| Code: | Width: | Power (LED): | Delivered lms (Width): | LPW: |
|-------|------------|--------------|------------------------|------|
| W25 | 635mm/25" | 20W | 2390 | 119 |
| W36 | 915mm/36" | 30W | 3584 | 119 |
| W48 | 1219mm/48" | 40W | 4780 | 119 |
| W60 | 1524mm/60" | 50W | 5974 | 120 |
| W72 | 1829mm/72" | 60W | 7168 | 119 |
| W84 | 2134mm/84" | 70W | 8364 | 120 |

C SPECIFY CCT/COLOR (OUTSIDE)

| | |
|-----|--------------------|
| T30 | 3000K (min 80 CRI) |
| T35 | 3500K (min 80 CRI) |
| T40 | 4000K (min 80 CRI) |
| TRD | Red |
| TGN | Green |
| TBL | Blue |

D SPECIFY CCT/COLOR (INSIDE)

| | |
|-----|--------------------|
| S30 | 3000K (min 80 CRI) |
| S35 | 3500K (min 80 CRI) |
| S40 | 4000K (min 80 CRI) |
| SRD | Red |
| SGN | Green |
| SBL | Blue |

E SPECIFY FINISH

| | |
|----|-----------------|
| BL | Black |
| MS | Metallic Silver |
| WH | White |

F SPECIFY LUMEN & WATTAGE REDUCTION

- PRO** Lumen & Wattage Reduction to approximately 25% of standard output
- PR1** Lumen & Wattage Reduction to approximately 50% of standard output
- PR2** Lumen & Wattage Reduction to approximately 75% of standard output



Additional Information

Note: Custom Reduction Percentages Available Upon Request.

EXAMPLE SPECIFICATION CODE

982510/T30/SRD/MS

DIMENSIONAL DIAGRAMS



APPROVALS

