

High Power

SEN Louvre CV 035

Code Table



Housing/ Finish	Cover/Lens	LED Type	Colour (CCT)	Length Availability	IP Rating	Connection Type	Mounting/ Finishing	Lens	Voltage
SEN Louvre CV Silver anodised	Clear Cover B	h -035 h035	2700K (90CRI) 27K	M 260-2010mm 250mm increments ³	IP54 54	1000mm Single tail d1	Rear Cable Exit 4	10° a	24V g
			3000K (90CRI) 30K			IP67 ¹ 67			
			3500K (80CRI) 35K		1000mm Single IP54 connector d5		30° c		
			4000K (80CRI) 40K		1000mm Double IP54 connector d6				
			5000K (80CRI) 50K		1000mm Single IP67 connector d7				
					1000mm Double IP67 connector d8				

¹ Due to the clear, flush potted polyurethane top layer on IP67 SEN Louvre CV 035 a colour shift of +/-20K should be expected

² Low adjustable bracket needs side cable exit option

³ L260mm – 1260mm max for UL

Code Example:

SVSA	-	B	-	h035	-	30K	-	M	1010	-	67	-	d2	-	4	-	c	-	g
SEN Louvre CV, Silver anodised		Clear Cover		h-line 035		3000K		1010mm		IP67			1000mm Double tail		Rear Cable Exit		30°		24V DC