

Linear

LiNi-S Glow Code Table



Housing/Finish	Cover/Lens	LED Type	Colour (CCT)	Length Availability	IP Rating	IP Rating/ Connection Type	Voltage		
LiNi-S Glow, Silver anodised	SGSA Diffused	C k- 209 ¹ k209	1900K	19K	LiNi-S Glow 209 M 94.4-2011mm 41.7mm increments	IP40 40	50mm Single IP20 connector	a3	24V DC g
			2100K	21K			50mm Double IP20 connector	a4	
			2300K	23K			300mm Single tail	c1	
			2500K	25K			300mm Double tail	c2	
			2700K	27K			300mm Single IP20 connector	c3	
			3000K	30K			300mm Double IP20 connector	c4	
			3500K	35K			1000mm Single tail	d1	
			4000K	40K			1000mm Double tail	d2	
			5000K	50K			1000mm Single IP20 connector	d3	
							1000mm Double IP20 connector	d4	

¹ LEDmix requires two colour temperature choices

LEDmix Code Example:

SGSA	-	C	-	k209	-	21	-	35	-	M 511	-	40	-	a4	-	g
LiNi Glow, Silver anodised		Diffused		k-line LEDmix 209		2100K		3500K		511mm		IP40		50mm Double IP20 connector		24V DC