



## GENERAL SPECIFICATION

**Body and trim:** Steel and aluminum.

**Finish:** Powder coated.

**Diffusers:** Opal polycarbonate.

**Drivers:** Integral, HPF electronic drivers for 120-277V (EU-240V), 0-10V, 1% dimming standard.

**Mechanical:** Luminaires mount directly over J box (by others - North America only).

**Integral Emergency system:** Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Not available with a 347V supply.

**L70 @25deg C (77deg F):** > 50,000 hrs.


**Delivered Lumens:** Delivered lumens & LPW based on 3000K (min 80 CRI).

**Approvals:** Damp Location (Indoor use only).


## MOUNTING & OPTICS




Ceiling




97 1010



97 1020



97 1030



97 1040

## HOW TO ORDER

### A SPECIFY LUMINAIRE

Code:	Diameter (A):	Power (LED):	Delivered lms:	LPW:
97 1010	457mm/18"	30W	3301	110
97 1020	610mm/24"	40W	4590	115
97 1030	914mm/36"	100W	11892	119
97 1040	1219mm/48"	199W	23697	119

### B SPECIFIED CCT

30	3000K (min 80 CRI)
35	3500K (min 80 CRI)
40	4000K (min 80 CRI)

### C SPECIFY FINISH

BL	Black
MS	Metallic Silver
WH	White
F39	Other painted finish (RAL number required)
F40	Other Non-RAL painted finish (sample chip required)

#### Additional Information

F39 & F40 have a one time set-up charge regardless of quantity.

### D SPECIFY LUMEN & WATTAGE REDUCTION

PRO	Lumen & Wattage Reduction to approximately 25% of standard output
PR1	Lumen & Wattage Reduction to approximately 50% of standard output
PR2	Lumen & Wattage Reduction to approximately 75% of standard output

#### Additional Information

Note: Custom Reduction Percentages Available Upon Request.

### E SPECIFY OPTIONS

EM	Integral Emergency System
----	---------------------------

## F SPECIFY DIMMING OPTIONS

- DL** DALI Dimming (1%)
- DS** DSI (EU only)
- SD** SwitchDim (EU only)

### Additional Information

DS & SD options not available in North America

**EXAMPLE SPECIFICATION CODE**

**971020/35/MS**

## DIMENSIONAL DIAGRAMS



## APPROVALS

