



LiNi XL Wallwasher 5T

Specification sheet



LED Pitch	12.95mm (0.51in)
Dimension	H62.5/W41.1/D241.6(149.2)mm (H2.46/W1.61/D9.51(5.87) in)
Chip	hcc-line CREE
Beam angle	92.5
Colours	2700K/3000K/4000K
Bin/Step	3 Step MacAdam ellipse
CRI	90
Lifetime	50,000 hours @ 25°C (50,000 hours @ 77°F)
Operating temp	T _a = -20°C to 40°C (T _c max = 80°C) T _a = -4 to 104°F (T _c max = 176°F)
IP rating	IP20
Finish	Matt white/Black paint
Cover/lens	Matt reflector
Mounting	Recessed mounting, Trimless type
Connection	Single IP20 Connector
Control	Constant current



PERFORMANCE DATA

Power Consumption	Supply voltage	Supply current
11W	16V	700mA

Colour Rendering Index (CRI)

	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14
2700K	91	92	94	92	90	90	93	82	51	83	91	79	92	95
3000K	93	95	96	95	92	96	94	81	61	92	93	80	94	98
4000K	90	93	94	94	92	93	93	81	50	86	93	77	90	97

Reflector		CRI	R9	Rf	Rg
hcc-line	500lm 45lm/W	93	63		

