






Luminaire designed for flush installation on floors in outdoors and indoors areas. Suitable for power LED sources. Its body is made of stainless steel and aluminum submitted to anodizing treatment up to 18 micron. Front diffuser in extra clear tempered glass, subjected to a specific anti-stain sandblasting treatment, is integral to the body through a special glue-sealant used in shipbuilding. The snap-in installation of the devices is allowed through the mounting of stainless steel casing. It has anti-vandal stainless steel springs that make the device particularly suitable for installation in public and private areas. The device is removable via dedicated disassembly key to be ordered separately. The luminaire is available in IP67 230Vac DALI dimmable and IP68 24Vdc. It is equipped with 0,5m long neoprene cable for connection to the power supply line, through appropriate waterproof connection systems not included.

*Apparecchio pensato per l'installazione ad incasso a filo su pavimenti in ambito esterno ed interno, finalizzato all'impiego di sorgenti LED ad alta luminosità. Corpo lampada realizzato in acciaio inox ed alluminio sottoposto a trattamento di anodizzazione fino a 18 micron. Diffusore frontale in vetro extra chiaro temperato e sottoposto a specifico trattamento di sabbiatura antimacchia, solidale al corpo per mezzo di apposito collante-sigillante di derivazione navale. L'installazione degli apparecchi è consentita mediante l'impiego ed il fissaggio dell'apposita controcassa in acciaio inox. La presenza di appositi sistemi antivandalo rendono l'apparecchio particolarmente indicato per installazioni in ambito pubblico e privato essendo asportabile solo per mezzo di chiave di smontaggio dedicata. Il prodotto è disponibile in versione IP67 con alimentazione 230VAC dimmerabile DALI e IP68 con alimentazione 24VDC. Completo di 0,5 metri di cavo in neoprene per il collegamento alla linea di alimentazione per mezzo di appositi sistemi di giunzione stagna non inclusi, da ordinare separatamente.*



### CERCHIO - IP 67

code/codice	model/modello	lamp/sorgente	total lumens/lumen totali		
			2700K	3000K	4000K
07.103817	C1	LED 15W	1188	1250	1375
07.103816	C2	LED 30W	2375	2500	2750
07.103815	C3	LED 45W	3572	3760	4136
07.103880	C4	LED 60W	4769	5020	5522
07.103881	C5	LED 76W	6033	6350	6985

### CERCHIO - IP 68

code/codice	model/modello	lamp/sorgente	total lumens/lumen totali		
			2700K	3000K	4000K
07.103849	C1	LED 15W	1188	1250	1375
07.103848	C2	LED 30W	2375	2500	2750
07.103847	C3	LED 45W	3572	3760	4136
07.103907	C4	LED 60W	4769	5020	5522
07.103908	C5	LED 76W	6033	6350	6985

### ACCESSORIES/ACCESSORI

code/codice	version/model
20.103934	C1 IP20 Housing / Controcassa IP20
20.103935	C2 IP20 Housing / Controcassa IP20
20.103936	C3 IP20 Housing / Controcassa IP20
20.103937	C4 IP20 Housing / Controcassa IP20
20.103938	C5 IP20 Housing / Controcassa IP20

### ACCESSORIES/ACCESSORI

code/codice	version/model
20.103992	C1 IP68 Housing / Controcassa IP68
20.103993	C2 IP68 Housing / Controcassa IP68
20.103994	C3 IP68 Housing / Controcassa IP68
20.103995	C4 IP68 Housing / Controcassa IP68
20.103996	C5 IP68 Housing / Controcassa IP68