



MTIK10 LED IP67

INTEGRAL DRIVER





Suspended/Surface mounted. Linear LED light with grey or black IP67 end caps.

A SLIM D SHAPED TUBULAR DESIGN.

The MTIK10 LED IP67 can be surface mounted with stainless steel clamps. The fitting can be used internally and externally and offers 180° light distribution through its polycarbonate satin diffuser.

The MTIK10 LED IP67 is an incredibly robust linear lighting solution, it makes use of efficient LED technology offering switched or Dali dimming options for a controllable level of light output.

Suitable for damp/wet areas not intended for permanent submersion.

Light Source Information

- LED/Electronic Driver.
- Available in 3000K & 4000K.

Options

- 3hr Emergency with Dali monitoring.
- Grey or black IP67 end caps.
- Available as through wired and plug and go.

Emergency available from size 4 upwards, HE only. Through wired and plug & go add 30mm to the length.

Dimming

1-10V or Dali.

Installation

Horizontal, angled suspension or surface mounted.

Optics

Satin or clear polycarbonate diffuser.



Stainless Steel Clamp



Tear Drop Suspension Kit



Black End Cap

Cat No.	Length (mm)	Lumens Clear	Lumens Satin	Circuit Power (W)
HIGH EFFICIENCY				
MTIK10 LED 2 HE	655	1250	1340	12
MTIK10 LED 3 HE	935	1950	1820	15
MTIK10 LED 4 HE	1215	2600	2040	20
MTIK10 LED 5 HE	1495	3410	3640	23
MTIK10 LED 6 HE	1775	4045	3670	27
HIGH OUTPUT				
MTIK10 LED 2 HO	655	3660	2555	22
MTIK10 LED 3 HO	935	5155	4190	32
MTIK10 LED 4 HO	1215	4735	5400	36
MTIK10 LED 5 HO	1495	7165	6590	45
MTIK10 LED 6 HO	1775	6995	8015	52



H 55mm
x W 57mm



Light output 180°

For further information

Call: +44 (0)1525 376974

Email: reply@encapsulite.co.uk

or visit www.encapsulite.co.uk